

TK SST2

DIGITAL TERRESTRIAL
TELEVISION DVB-T/T2 H265
HD RECEIVER

Teknomak

REFERENCIA	TK SST2
Main system	
CPU Speed	600 MHz
Flash Memory	32M bit
DDR3	512M bit
Tuner & Demodulator	
ANT. Connector	IEC TYPE, female
Loop Output	IEC TYPE, male
Input Frange range	50.5--858MHz
Input Impedance	75 Ω
Input Signal level	-82 dBm to -20 dBm (average power)
Audio/video data in/out	
AV output:	Scart
HDMI	Salida HDMI
Coaxial	Audio coaxial
LAN	Puerto LAN RJ45
Operation Environment	
Operation temperature	+0° - 70°
Storage temperature	-40° - +65°
Mpeg Audio/ Video Decoding	
Video	MPEG-2 (ISO/IEC 13818-2) MPEG-4 (ISO/IEC 14496-2) H.264 (ISO/IEC 14496-10) H.265 HEVC (Max 10bit)
Profile Level	MPEG-2 MP@HL MPEG-4 ASP@L5 HD H.264HP@L4.1 * HEVC (max 10 bit) main profile @level 4.1, main 10 profile @level 4.1
Input rate	Max. 60M bits
Aspect ratio	4:3, 16:9, Auto
Video Resolution	1920*1080i; 1280*720p; 720*576i
Audio decoding	MPEG-1 Layer I/II, MPEG-2 layer I/II, AAC, AAC+/HE-AAC/AC3, Dolby plus
Audio mode	Mono/Left/Right/Stereo
Sample rate	32, 44.1 & 48 KHz
Power supply	
Input voltage	AC100--240V, 50/60Hz Or 12V/1A
Type	AC/ DC Power

